



Artisan Oak 04

Element7's Artisan Collection of reclaimed oak flooring has been hand-crafted and showcases the natural beauty of the oak planks, featuring the intricate grain patterns and unique characteristics of each board. Our Artisan manufacturers create a bespoke finished product to meet the client's needs. The warm, inviting tones of the oak create a timeless look that complements any décor style

| | |
|---|--|
| Product Name | Artisan Oak 04 |
| Botanical Name | Quercus Robur |
| Source | Old structures including from restored residences and churches |
| Installation Method | Bonded onto a levelled sub floor construction which can be a screeded or suspended floor |
| Installation on Underfloor Heating | Suitable for use with hot water or electrical underfloor heating |
| Structure | 2 or 3 Layer 14mm, 15mm, or 16mm 1 st layer, Wear Layer: 4mm, 5mm or 6mm Oak 2 nd layer, Spruce 3 rd layer, Counterbalance plate: Spruce (perpendicular to the first layer for ultimate stability) |
| Finish | Different surface options are available which can be left unfinished or treated with 2/3 coats of water-based varnish or natural oil. |
| Cleaning & Care | Damp clean with a cotton mop and pH neutral white floor soap for whole floor clean or just a damp cloth for spot cleaning. |

| | |
|----------------------|---|
| Prime Grade | The planks are predominantly free of knots and sapwood, some will exhibit isolated small sound knots or filled small knots and filled small stress cracks. |
| Knotty Grade | The planks predominantly feature sound knots, some will exhibit filled knots, filled splits, possible insect marks and filled stress cracks. |
| Country Grade | The planks predominantly feature most characteristics, including, sound knots, filled knots, filled cracks, filled stress cracks sapwood and possible insect marks. |
| Reclaimed | Characterized by the presence of large knots, darkening, curvature of fibers and shine pattern, in different directions and tonalities, inactive woodworms' holes, inserts and differing surfaces due to the restoration of old wood. |

EXCEPTIONALLY ENGINEERED WOOD FLOORING

| | |
|----------------------|---|
| Board Width | Available in mixed widths |
| Board Length | Mixed lengths ranging from 500mm -2500mm (19 44/64 - 98 27/64). |
| Styles | Plank, Herringbone and patterns on request |
| Manufacture | Manufactured in Italy exclusively for Element7 |
| Standards | UNI EN 13489 Multi-layer parquet elements Density (kg/mc) 665 Thickness 14mm (35/64), 15mm (38/64) and 16mm (40/64) (+/- 0.5 mm = 1/64) Reaction to fire: Cfl-s1 Formaldehyde emissions: E1 Janka Hardness: 4980N Slipperiness: R11 Thermal resistance: 0.08M2 K/W@ 14mm, 0.10M2 K/W @ 15mm, 0.13M2 K/W @ 16mm Biological durability: Class 1-5 |
| Certification | All raw materials are sustainably sourced and FSC® and PEFC Certified FSC Certificate Number INT-COC-003944, INT-CW-003944 PEFC Certificate Number INT-PEFC-COC-1119 |



**Please note Imperial measurements are shown in brackets and expressed in inches rounded to the nearest 1/64 fraction.*

Please note: Wood is a natural product, and each plank is a unique specimen, hence planks may differ one from the other and batch to batch in colour. Wood is a natural product and as with all natural products it may fade naturally from excessive exposure to UV light.

The information herein is believed to be true and accurate at the time of publication and Element7 accepts no liability for any error in any specification provided.

Issue Date: April 2024 R

Please Note Whilst our sampling and photography endeavors to show the grain and colour as natural as possible a sample or photo are never an exact representation of the appearance of the appearance of the finished entire floor