EXCEPTIONALLY ENGINEERED WOOD FLOORING





Black Wenge

An Element7 floor lasts a lifetime without the need for refinishing, retaining its stunning original colour throughout. This is achieved by the uncompromising use of only the very best raw materials and technical superiority of the finishes. Wenge is pre-finished with a pure natural look and feel. Characteristically straight grained, can be finished in natural mid brown or dark brown tones.

Product Name Black Wenge

Botanical Name Millettia Laurentii

Origin Central Africa

Installation Method Bonded onto a levelled sub floor construction which

can be a screeded or suspended floor

Installation on Suitable for use with hot water or electrical underfloor

Underfloor Heating heating

Structure 3 Layer 15mm or 20mm

1st layer, Wear Layer: 4mm (+/-) 0.5mm Hardwood 2nd layer, Core: Birch Plywood or Austrian Fir 3rd layer, Counterbalance plate: Austrian Fir

(perpendicular to the first layer for stability)

Brushed surface treated with 8 coats of water-based

varnish which never needs refinishing when

maintained correctly.

Damp clean with a cotton mop and pH neutral floor

soap for whole floor clean or just a damp cloth for

spot cleaning.

Prime Grade The planks are predominantly free of knots and sapwood, some will exhibit isolated small sound knots or

Cleaning & Care

Finish

filled small knots and filled small stress cracks.

Knotty Grade The planks predominantly feature sound knots, some will exhibit filled knots, filled splits, possible insect

marks and filled stress cracks.

Country Grade The planks predominantly feature most characteristics, including, sound knots, filled knots, filled cracks,

filled stress cracks sapwood and possible insect marks.

Reclaimed Characterized by the presence of large knots, darkening, curvature of fibers and shine pattern, in different

directions and tonalities, inactive woodworms' holes, inserts and differing surfaces due to the restoration of

old wood.

EXCEPTIONALLY ENGINEERED WOOD FLOORING



Board Width* Available in mixed widths between 150mm-300mm (5 58/64 – 11 52/64)

Fixed widths are subject to availability.

Board Length* Typically, 1000mm – 3000mm (39 24/64 – 118 7/64)

Styles Plank, Chevron, Herringbone, Parquet Patterns, Panels and Bespoke Designs

Manufactured in Italy exclusively for Element7.

Standards UNI EN 13489 Multi-layer parquet elements

Density (kg/mc) 665

Thickness 15mm or 20 mm (38/64 or 50/64) (+/- 0.5 mm - 1/64) subject to selected format

Reaction to fire: Cfl-s1 Formaldehyde emissions: E1

Janka Hardness: 7300N

Slipperiness: R11

Thermal resistance: 0.10M2 K/W @15mm, 0.17M2 K/W @20mm

Biological durability: Class 1-5

Certification All raw materials are sustainably sourced and FSC® and PEFC Certified

FSC Certificate Number INT-COC-003944, INT-CW-003944

PEFC Certificate Number INT-PEFC-COC-1119





*Please note Imperial measurements are shown in brackets and expressed in inches rounded to the nearest 1/64 fraction.

Please note: Wood is a natural product, and each plank is a unique specimen, hence planks may differ one from the other and batch to batch in colour. Wood is a natural product and as with all natural products it may fade naturally from excessive exposure to UV light.

The information herein is believed to be true and accurate at the time of publication and Element7 accepts no liability for any error in any specification provided.