EXCEPTIONALLY ENGINEERED WOOD FLOORING





C20

An Element7 floor lasts a lifetime without the need for refinishing, retaining its stunning original colour throughout. This is achieved by the uncompromising use of only the very best raw materials and technical superiority of the finishes. C20 is pre-finished with a pure and natural oiled look and feel with a golden brown patina.

Product Name C20

Botanical Name Quercus petraea/robur

Origin European Oak

Installation Method Bonded onto a levelled sub floor construction which

can be a screeded or suspended floor

Installation on Suitable for use with hot water or electrical underfloor

Underfloor Heating heating

Structure 3 Layer, 15mm or 20mm (also available as 2 Layer in

11mm)

1st layer, wear layer: 5mm (+/-) 0.5mm Oak

2nd layer, Core: European Spruce

3rd layer, Counterbalance plate: European Oak

Finish Brushed surface treated with 2 coats of natural oil.

Further coats can be applied after installation for

additional protection.

Cleaning & Care Damp clean with a cotton mop and pH neutral floor

soap for whole floor clean or just a damp cloth for spot cleaning. Follow care and maintenance for oiled

floors.

Prime Grade Criteria The planks are predominantly free of knots and sapwood, some will exhibit isolated small sound knots or

filled small knots and filled small stress cracks.

Knotty Grade The planks predominantly feature sound knots, some will exhibit filled knots, filled splits, possible insect

marks and filled stress cracks.

Country Grade The planks predominantly feature most characteristics, including, sound knots, filled knots, filled cracks,

filled stress cracks sapwood and possible insect marks.

Reclaimed Characterized by the presence of large knots, darkening, curvature of fibers and shine pattern, in different

directions and tonalities, inactive woodworms' holes, inserts and differing surfaces due to the restoration of

old wood.

EXCEPTIONALLY ENGINEERED WOOD FLOORING



Board Width* Available in 165mm (6 32/64), 192mm (7 36/64), 200mm, (7 56/64) 240mm (9 29/64) and 290mm

(11 27/64), 340mm (13 25/64).

Board Length* Typically, 1200mm – 2800mm (47 16/64 – 110 15/64) (Longer options up to 6 metres (236 14/64) are

available subject to material availability)

Styles Plank, Chevron, Herringbone, Parquet Patterns, Panels and Bespoke Designs

Manufactured in Italy exclusively for Element7.

Standards UNI EN 14342 :2013 Multi-layer parquet elements

Density (kg/mc) 660

Thickness 20mm (50/64), 15mm (38/64) and 11mm (28/64) (+/- 0.5 mm) (1/64)

Reaction to fire: Cfl-s1

Formaldehyde emissions: E1 Janka Hardness: 4980N

Slipperiness: R11

Thermal resistance: 0.17M2 K/W@20mm, 0.10M2 K/W@15mm, 0.06M2 K/W@11mm

Biological durability: Class 1-5

Certification All raw materials are sustainably sourced and FSC® and PEFC Certified

FSC Certificate Number INT-COC-003944, INT-CW-003944

PEFC Certificate Number INT-PEFC-COC-1119





*Please note Imperial measurements are shown in brackets and expressed in inches rounded to the nearest 1/64 fraction.

Please note: Wood is a natural product, and each plank is a unique specimen, hence planks may differ one from the other and batch to batch in colour. Wood is a natural product and as with all natural products it may fade naturally from excessive exposure to UV light.

The information herein is believed to be true and accurate at the time of publication and Element7 accepts no liability for any error in any specification provided.