



Elephant Grey Oak

An Element7 floor lasts a lifetime without the need for refinishing, retaining its stunning original colour throughout. This is achieved by the uncompromising use of only the very best raw materials and technical superiority of the finishes. Elephant Grey Oak is pre-finished with a pure natural look and feel with a warm dark brown patina..

Product Name	Elephant Grey Oak
Botanical Name	Quercus Robur
Origin	European Oak
Installation Method	Bonded onto a levelled sub floor construction which can be a screeded or suspended floor
Installation on Underfloor Heating	Suitable for use with hot water or electrical underfloor heating
Structure	3 Layer 16mm (also available as a 2 Layer) 1 st layer, Wear Layer: 4mm (+/-) 0.5mm Hardwood Oak 2 nd layer, Core: Birch Plywood 3 rd layer, Counterbalance plate: Austrian Fir (perpendicular to the first layer for stability)
Finish	Brushed surface treated with 8 coats of water-based varnish which never needs refinishing when maintained correctly.
Cleaning & Care	Damp clean with a cotton mop and pH neutral floor soap for whole floor clean or just a damp cloth for spot cleaning.

Prime Grade	The planks are predominantly free of knots and sapwood, some will exhibit isolated small sound knots or filled small knots and filled small stress cracks.
Knotty Grade	The planks predominantly feature sound knots, some will exhibit filled knots, filled splits, possible insect marks and filled stress cracks.
Country Grade	The planks predominantly feature most characteristics, including, sound knots, filled knots, filled cracks, filled stress cracks sapwood and possible insect marks.
Reclaimed	Characterized by the presence of large knots, darkening, curvature of fibers and shine pattern, in different directions and tonalities, inactive woodworms' holes, inserts and differing surfaces due to the restoration of old wood.

Issue Date: April 2024 |

Please Note Whilst our sampling and photography endeavours to show the grain and colour as natural as possible a sample or photo are never an exact representation of the appearance of the appearance of the finished entire floor

EXCEPTIONALLY ENGINEERED WOOD FLOORING

Board Width	Available in 140mm (5 33/64), 185mm (7 18/64), 230mm (9 4/64), 280mm (11 2/64) and 390mm (15 23/64).
Board Length	Typically, 1000mm – 3000mm (39 24/64 – 118 7/64)
Styles	Plank, Chevron, Herringbone, Parquet Patterns, Panels and Bespoke Designs
Manufacture	Manufactured in Italy exclusively for Element7.
Standards	UNI EN 13489 Multi-layer parquet elements Density (kg/mc) 630 Thickness 16 mm (40/64) (+/- 0.5 mm / 1/64) Reaction to fire: Cfl-s1 Formaldehyde emissions: E1 Janka Hardness: 4980N Slipperiness: R11 Thermal resistance: 0.13M2 K/W Biological durability: Class 1-5
Certification	All raw materials are sustainably sourced and FSC® and PEFC Certified FSC Certificate Number INT-COC-003944, INT-CW-003944 PEFC Certificate Number INT-PEFC-COC-1119



**Please note Imperial measurements are shown in brackets and expressed in inches rounded to the nearest 1/64 fraction.*

Please note: Wood is a natural product, and each plank is a unique specimen, hence planks may differ one from the other and batch to batch in colour. Wood is a natural product and as with all natural products it may fade naturally from excessive exposure to UV light.

The information herein is believed to be true and accurate at the time of publication and Element7 accepts no liability for any error in any specification provided.

Issue Date: April 2024 |

Please Note Whilst our sampling and photography endeavours to show the grain and colour as natural as possible a sample or photo are never an exact representation of the appearance of the appearance of the finished entire floor