## EXCEPTIONALLY ENGINEERED WOOD FLOORING





## Italian Walnut

An Element7 floor lasts a lifetime without the need for refinishing, retaining its stunning original colour throughout. This is achieved by the uncompromising use of only the very best raw materials and technical superiority of the finishes. Italian Walnut is pre-finished with a pure and natural look and feel and has a dark brown patina.

Product Name Italian Walnut

Botanical Name Juglans Nigra

Origin American Walnut

Installation Method Bonded onto a levelled sub floor construction which

can be a screeded or suspended floor

Installation on Suitable for use with hot water or electrical underfloor Underfloor Heating heating

**Structure** 3 Layer 16mm and 20mm (Also available as 2 Layer)

1<sup>st</sup> layer, Wear Layer: 4.5mm (+/-) 0.5mm Walnut

2<sup>nd</sup> layer, Core: Fir Blocks (perpendicular)3<sup>rd</sup> layer, Counterbalance plate: Austrian Fir

Finish Sanded surface treated with 8 coats of varnish which

never needs refinishing when maintained correctly.

Cleaning & Care Hoover, sweep or damp clean with a cotton mop and

pH neutral floor soap for whole floor clean or just a

damp cloth for spot cleaning.

Prime Grade

The planks are predominantly free of knots and sapwood, some will exhibit isolated small sound knots or

filled small knots and filled small stress cracks.

Knotty Grade The planks predominantly feature sound knots, some will exhibit filled knots, filled splits, possible insect

marks and filled stress cracks.

Country Grade The planks predominantly feature most characteristics, including, sound knots, filled knots, filled cracks,

filled stress cracks sapwood and possible insect marks.

**Reclaimed** Characterized by the presence of large knots, darkening, curvature of fibers and shine pattern, in different

directions and tonalities, inactive woodworms' holes, inserts and differing surfaces due to the restoration of

old wood.

## EXCEPTIONALLY ENGINEERED WOOD FLOORING



Board Width\* Available in 180mm (7 6/64), 200mm (7 56/64), 240mm (9 29/64) and 300mm (11 52/64).

Board Length\* Typically, 1400mm – 2700mm (55 8/64 – 106 19/64). Product will be supplied within the quoted range.

Exact lengths are subject to raw material (Longer options up to 3.5 metres (137 51/64) are available

subject to material availability).

Styles Plank, Chevron, Herringbone, Parquet Patterns, Panels and Bespoke Designs

Manufactured in Italy exclusively for Element7.

Standards UNI EN 13489 Multi-layer parquet elements

Density (kg/mc) 560

Thickness 16mm (40/64) and 20mm (50/64) (+/- 0.5 mm - 1/64)

Reaction to fire: Cfl-s1

Formaldehyde emissions: E1

Janka Hardness: 4500N

Slipperiness: R11

Thermal resistance: 0.13M<sup>2</sup> K/W @16mm, 0.17M2K/W @ 20mm

Biological durability: Class 1-5

Certification All raw materials are sustainably sourced and FSC® and PEFC Certified

FSC Certificate Number INT-COC-003944, INT-CW-003944

PEFC Certificate Number INT-PEFC-COC-1119





\*Please note Imperial measurements are shown in brackets and expressed in inches rounded to the nearest 1/64 fraction.

**Please note**: Wood is a natural product, and each plank is a unique specimen, hence planks may differ one from the other and batch to batch in colour. Wood is a natural product and as with all natural products it may fade naturally from excessive exposure to UV light.

The information herein is believed to be true and accurate at the time of publication and Element7 accepts no liability for any error in any specification provided.