



New Light Oak

An Element7 floor lasts a lifetime without the need for replacement, retaining its stunning original colour throughout. This is achieved by the uncompromising use of only the very best raw materials and technical superiority of the finishes. New Light Oak has a varnished finish with a pure natural look and feel and has a warm light brown tone.

| | |
|---|--|
| Product Name | New Light Oak |
| Botanical Name | Quercus Robur |
| Origin | European Oak |
| Installation Method | Bonded onto a levelled sub floor construction which can be a screeded or suspended floor |
| Installation on Underfloor Heating | Suitable for use with hot water or electrical underfloor heating |
| Structure | 3 Layer 15mm or 20mm options 1 st layer, Wear Layer: 4mm (+/-) 0.5mm Oak 2 nd layer, Austrian Fir Block Board Core 3 rd layer, Counterbalance plate: Fir (perpendicular to the first layer for ultimate stability) |
| Finish | Brushed surface treated with 8 coats of water-based varnish which never needs refinishing when maintained correctly. |
| Cleaning & Care | Damp clean with a cotton mop and pH neutral white floor soap for whole floor clean or just a damp cloth for spot cleaning. |

| | |
|----------------------|---|
| Prime Grade | The planks are predominantly free of knots and sapwood, some will exhibit isolated small sound knots or filled small knots and filled small stress cracks. |
| Knotty Grade | The planks predominantly feature sound knots, some will exhibit filled knots, filled splits, possible insect marks and filled stress cracks. |
| Country Grade | The planks predominantly feature most characteristics, including, sound knots, filled knots, filled cracks, filled stress cracks sapwood and possible insect marks. |
| Reclaimed | Characterized by the presence of large knots, darkening, curvature of fibers and shine pattern, in different directions and tonalities, inactive woodworms' holes, inserts and differing surfaces due to the restoration of old wood. |

Issue Date: April 2024 MF

Please Note Whilst our sampling and photography endeavors to show the grain and colour as natural as possible a sample or photo are never an exact representation of the appearance of the appearance of the finished entire floor

EXCEPTIONALLY ENGINEERED WOOD FLOORING

| | |
|----------------------|---|
| Board Width* | Available in mixed widths between 150mm-300mm (5 58/64 – 11 52/64) Fixed widths are subject to availability. |
| Board Length* | Typically, 1000mm – 3000mm (39 24/64 – 118 7/64) |
| Styles | Plank, Chevron, Herringbone, Parquet Patterns, Panels and Bespoke Designs |
| Manufacture | Manufactured in Italy exclusively for Element7. |
| Standards | UNI EN 13489 Multi-layer parquet elements Density (kg/mc) 665 Thickness 15mm or 20 mm (38/64 or 50/64) (+/- 0.5 mm – 1/64) subject to selected format Reaction to fire: Cfl-s1 Formaldehyde emissions: E1 Janka Hardness: 7300N Slipperiness: R11 Thermal resistance: 0.10M2 K/W @15mm, 0.17M2 K/W @20mm Biological durability: Class 1-5 |
| Certification | All raw materials are sustainably sourced and FSC® and PEFC Certified FSC Certificate Number INT-COC-003944, INT-CW-003944 PEFC Certificate Number INT-PEFC-COC-1119 |



**Please note Imperial measurements are shown in brackets and expressed in inches rounded to the nearest 1/64 fraction.*

Please note: Wood is a natural product, and each plank is a unique specimen, hence planks may differ one from the other and batch to batch in colour. Wood is a natural product and as with all natural products it may fade naturally from excessive exposure to UV light.

The information herein is believed to be true and accurate at the time of publication and Element7 accepts no liability for any error in any specification provided.

Issue Date: April 2024 MF

Please Note Whilst our sampling and photography endeavors to show the grain and colour as natural as possible a sample or photo are never an exact representation of the appearance of the appearance of the finished entire floor