



Pale Walnut (F)

An Element7 floor lasts a lifetime without the need for refinishing, retaining its stunning original colour throughout. This is achieved by the uncompromising use of only the very best raw materials and technical superiority of the finishes. Pale Walnut is pre-finished with a pure and natural look and feel and has a warm light to mid brown patina.

Product Name	Pale Walnut (F)
Botanical Name	Juglans Nigra
Origin	American Walnut
Installation Method	Bonded onto a levelled sub floor construction which can be a screeded or suspended floor
Installation on Underfloor Heating	Suitable for use with hot water or electrical underfloor heating
Structure	3 Layer 16mm and 20mm (Also available as 2 Layer) 1 st layer, Wear Layer: 4.5mm (+/-) 0.5mm Walnut 2 nd layer, Core: Fir Blocks (perpendicular) 3 rd layer, Counterbalance plate: Austrian Fir
Finish	Sanded surface treated with 8 coats of varnish which never needs refinishing when maintained correctly.
Cleaning & Care	Hoover, sweep or damp clean with a cotton mop and pH neutral floor soap for whole floor clean or just a damp cloth for spot cleaning.

Prime Grade Criteria	The planks are predominantly free of knots and sapwood, some will exhibit isolated small sound knots or filled small knots and filled small stress cracks.
Knotty Grade	The planks predominantly feature sound knots, some will exhibit filled knots, filled splits, possible insect marks and filled stress cracks.
Country Grade	The planks predominantly feature most characteristics, including, sound knots, filled knots, filled cracks, filled stress cracks sapwood and possible insect marks.
Reclaimed	Characterized by the presence of large knots, darkening, curvature of fibers and shine pattern, in different directions and tonalities, inactive woodworms' holes, inserts and differing surfaces due to the restoration of old wood.

Issue Date: April 2024 F

Please Note Whilst our sampling and photography endeavour to show the grain and colour as natural as possible a sample or photo are never an exact representation of the appearance of the appearance of the finished entire floor

EXCEPTIONALLY ENGINEERED WOOD FLOORING

Board Width*	Available in 180mm (7 6/64), 200mm (7 56/64), 240mm (9 29/64) and 300mm (11 52/64).
Board Length*	Typically, 1400mm – 2700mm (55 8/64 – 106 19/64). Product will be supplied within the quoted range. Exact lengths are subject to raw material (Longer options up to 3.5 metres (137 51/64) are available subject to material availability).
Styles	Plank, Chevron, Herringbone, Parquet Patterns, Panels and Bespoke Designs
Manufacture	Manufactured in Italy exclusively for Element7.
Standards	UNI EN 13489 Multi-layer parquet elements Density (kg/mc) 560 Thickness 16mm (40/64) and 20mm (50/64) (+/- 0.5 mm - 1/64) Reaction to fire: Cfl-s1 Formaldehyde emissions: E1 Janka Hardness: 4500N Slipperiness: R11 Thermal resistance: 0.13M ² K/W @16mm, 0.17M ² K/W @ 20mm Biological durability: Class 1-5
Certification	All raw materials are sustainably sourced and FSC® and PEFC Certified FSC Certificate Number INT-COC-003944, INT-CW-003944 PEFC Certificate Number INT-PEFC-COC-1119



**Please note Imperial measurements are shown in brackets and expressed in inches rounded to the nearest 1/64 fraction.*

Please note: Wood is a natural product, and each plank is a unique specimen, hence planks may differ one from the other and batch to batch in colour. Wood is a natural product and as with all natural products it may fade naturally from excessive exposure to UV light.

The information herein is believed to be true and accurate at the time of publication and Element7 accepts no liability for any error in any specification provided.

Issue Date: April 2024 F

Please Note Whilst our sampling and photography endeavour to show the grain and colour as natural as possible a sample or photo are never an exact representation of the appearance of the appearance of the finished entire floor